



# **STEF JOINT COMPOUND WATERPROOFING**

## **1-PRODUCT DESCRIPTION:**

Stef joint compound waterproofing provides professional-grade performance. All Purpose Joint Compound convenience with good taping and topping performance. Recommended for waterproofing walls against water and moisture and repairing cracks in interior plaster and masonry , these compounds features great open time and cold bond, and has smooth and slick properties. This joint compound qualifies as a low VOC emitting material and complies with ASTM C475.

## **2-PRODUCT FEATURES**

- Durable
- Low Shrinkage Cracks
- Extra fine smooth finishing solutions
- Excellent Workability

## **3-LIMITATIONS:**

**STEF JOINT COMPOUND** is for interior applications only. Ambient, surface and material temperatures must be above 13°C. (55°F) during application and for minimum 48 hours after application.

## **4-MIXING PROCEDURE:**

Mix compound in original container prior to use.

Discard all materials which have begun to harden.

**DO NOT SUBSTITUTE NOR COMPENSATE STEF JOINT COMPOUND WITH WATER OR OTHER ADDITIVES.**

## **5-APPLICATION:**

Cement surfaces must be clean and sound, free of weak and powdery surfaces, dust, dirt, oil, grease and any other deleterious materials detrimental to a positive bond.

Thinning the compound is not recommended. However if job conditions require a thinner compound, add potable water, up to maximum 1 quart per gallon of compound and mix.

Allow compound to dry thoroughly between coats

## **6-CLEAN UP:**

Clean all tools promptly after each use with water. Do not allow mixes to dry on tools.

## **7-STORAGE:**

Store **STEF JOINT COMPOUND** in a dry,

vented, waterproof location, stacked off the ground with ambient temperatures above 13°C (55°F).

Keep materials dry, protected from rapid temperature changes, dampness and moisture and away from direct sunlight.

KEEP FROM FREEZING.

**PACKAGING:** **STEF JOINT COMPOUND** is readily available in 17 Lt and 4 litres pails. It is available in white

### **TECHNICAL DATA**

**Product type:** Ready mixed, non cementitious calcium carbonate

**Appearance:** Thick white paste

**Toxicity:** Non-toxic

### **Performance Characteristics:**

**Mixing ratio:** No mixing required ready mixed. Small amount of water can be added to desired consistency.

**Coverage:** Coverage will vary according to texture method of application.

**Average consumption:** 1 box per 10.2 m<sup>2</sup> (500 ft<sup>2</sup>) drywall taped.

**Substrate requirement:** Clean solid drywall or cement wall.



Bsous, Street 505, Aley Mount Lebanon | +961 71 779 922 | [info@Stef-me.com](mailto:info@Stef-me.com) | [www.Stef-me.com](http://www.Stef-me.com)