



COURT PAINT

*(FINE & REGULAR)
(Colored Acrylic Coating)*

1- Product Description

STEF Court Paint is a color coating with a yogurt consistency which contains 100% acrylic resins, inorganic pigments, titanium pigments, fine marble aggregates, other additives, and high performance fungicides and stabilizers. The product is available in colors with fine or regular textures and specially formulated for roller application.

2- Use

STEF Court Paint has been specially designed for application on surfaces such as concrete panels, concrete, concrete structures, floors, stairs.

3- Coverage

The type of surface on which **STEF Court Paint** is applied and the temperature can greatly influence the area covered with one container.

For 2 layers:

17 L covers \pm 40 m²

4- Mix

STEF Court Paint may be diluted with water to ease its application.

Maximum 1 L of water per 17 L container

5- Application

Consult the substrates sheets for the type of application in compliance with your type of surface on our website. This is a list of the different substrates: concrete, stamped concrete, concrete panels.

Apply the product early in the morning or in the shade at a temperature between 12 and 26°C (54 – 79°F). The surface must be completely dry. Ensure weather forecast does not predict rain for 6 to 8 hours after application.

It is important to ensure that the target surface is not covered with a material (sealing, paint, epoxy, etc.) that would affect the adhesion properties.

The surface requiring coating must be dry and free of dust, oil, grease, wax or any other material or product that may prevent adhesion of the **STEF Court Paint**.

It is recommended to clean the surface with **STEF Concrete Conditioner** before applying **STEF Court Paint**.

If repairs are needed, use appropriate **T**products.

STEF Court Paint will never be stronger than the surface on which it is installed. If the surface is in poor condition, there will be no adhesion.

Thoroughly mix the container and apply using a:

- **Brush:** provides a smoother finish than a roll. The bristles length of the brush will affect the texture. Brush the corners of your surfaces.
- **Roll:** 10 mm thickness (the longer the bristles, the rougher the result) if you want to have an even more granular texture, pass a dry roller before the coating dries, it will raise the grains even more.
- **Gravity Gun:** Apply 2 layers of coating and wait 24 hours between each coat.

Note: The surface must be protected against bad weather. Allow a curing period of at least 12 hours before walking on the coated surface and 78 hours before placing furniture on the surface. The coating curing period is 28 days

The code states that the thickness of the finish coat should be less than 1 mm to be approved in the non combustible construction. **STEF Court Paint** Finish texture is less than 1 mm and as such complies with Article 3.1 .5.2. (1) (a) of the National Building Code of Canada.

6- Cleaning

The tools used for applying the **STEF Court Paint** color coating can be cleaned with water while the product is still wet.

7- Personal Protection

When using , it is recommended to wear the following safety equipment:

- Safety goggles or protective glasses
- Chemical resistant gloves
- Long sleeves and/or rubber based protective clothing
- **8- Storage/Shelf Life**
-
- Store **STEF Court Paint** at a controlled temperature ranging from 5 to 30°C (41 to 86°F) in a closed plastic container. Keep away from frost. Product lifetime is of 2 to 3 years.
-
- **9- Transport conditions**
-
- Shipping Name: Not applicable.
- TDG Classification: Not regulated.
-
- **Note:** This product requires no special measures during International transport.
-
- **10- Quality Control**
-
- All manufactured products are subject to rigorous quality control procedures during and after the manufacturing process

