



STEF DURAFLOOR

1. Description

DuraFloor is a ready-to-use, solvent-based floor coating designed for long-lasting protection and aesthetics. It provides, excellent adhesion to concrete, and high resistance to abrasion, chemicals, and weathering. Available in several colors.

2. Key Features

- Hardness & durability
- Excellent adhesion to concrete and masonry
- Resistant to water, detergents, and mild chemicals
- Fast drying, easy application (brush, roller, or spray)
- High gloss & color retention
- Available in 96 tinted shades

3. Technical Data (Typical Values)

- **Solvent:** Xylene
- **Solid content:** ~50–55% (by weight)
- **Viscosity:** 200–600 cP @ 25 °C (Brookfield)
- **Density:** 0.95–1.05 g/cm³
- **Touch dry:** 15–30 minutes
- **Hard dry:** 2–3 hours
- **Recoating interval:** 4–6 hours
- **Coverage:** 4–6 m²/L (depending on substrate porosity)
- **Finish:** Gloss / Semi-gloss
-

4. Applications

- Industrial floors & warehouses
- Parking garages & workshops
- Commercial decorative floors
- Protective coating for concrete
-

5. Packaging

- 5 L / 17 L metal pails
-

6. Storage & Shelf Life

Store tightly sealed in a ventilated, shaded area. Keep away from direct sunlight, heat, and ignition sources. Shelf life: **12 months** in original container.

