



Stef Seal

(Curing & sealant agent)

1- Description

Stef Seal is a solvent-based acrylic sealant. It does not make white spots on contact with water and dries quickly under normal conditions of application.

Stef Seal enables concrete to develop its full potential in terms of increased strength, durability, sealing and wear resistance.

Stef Seal has been specially designed to optimally protect acrylic coatings, pavers, cement and fresh concrete. Once the sealer is dry, it will help preserve the natural color and prevent dirt pick-up.

2- Characteristics & Advantages

Characteristics	Advantages
Good water resistance	Does not bleach when immersed
Good abrasion resistance	Reduces tire marks
Good UV resistance	Does not degrade upon exposure to sunlight
Easy to apply	Apply with a roller, a brush or spray

3- Coverage

The quantity to apply will depend on the surface, texture and porosity of the concrete.

Regular concrete:

3.78 L covers $\pm 15 \text{ m}^2$ (1 gal covers $\pm 162 \text{ ft}^2$)

18.9 L covers $\pm 75,6 \text{ m}^2$ (5 gal covers $\pm 814 \text{ ft}^2$)

Porous concrete:

3.78 L covers $\pm 12,6 \text{ m}^2$ (1 gal covers $\pm 136 \text{ ft}^2$)

18.9 L covers $\pm 63 \text{ m}^2$ (5 gal covers $\pm 678 \text{ ft}^2$)

4- Application

Apply the product early in the morning or in the shade. Avoid rain during application and drying. Concrete and air temperature should be between 12 and 25°C. High humidity and no wind may increase the required drying time.

The concrete must be clean and free of oil, grease, debris and dirt. Use a pressure washer and the appropriate *Stef* product to obtain a clean surface

Before the application of *Stef Seal* the surface must be completely dry. A fresh acrylic coating should dry for 72 hours minimum before applying *Stef Seal*.

Because of the solvents present, any application of this sealant on a water-based coating that has not completely dried will result in a peel and possible stripping of the coating.

Stef Seal is easy to use. It can be applied by roller, sprayer (hand or electric) or sheepskin. Use the container directly without diluting and apply a uniform and even coat. Avoid excessive accumulation of product. Respect the recommended quantities. Wait 24 hours between each layer.

Note:

For use in a garage, wait 3 weeks before entering the cars.

Maintenance: Over time, traffic will use *Stef Seal* sealant. It is recommended to reapply the product to 3 or 4 years if necessary.



Bsous, Street 505, Aley Mount Lebanon | +961 71 779 922 | info@Stef-me.com | www.Stef-me.com